



FEATURES

- 2nd Generation S-LOCK Securing System
- Unique rotary switch and low profile C13 locking mechanism fits any standard C14 inlet
- Rated up to 15 Amps
- Various colors / length available
- Patent Pending



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG For Europe : 0.75mm ² / 1.0 mm ²

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



ORDERING INFORMATION

514830 - XX XYZ X










S-Lock Series No.

WIRE TYPE:
For North America:
94=18AWG/SVT, 95=18AWG/SJT
85=16AWG/SJT, 75=14AWG/SJT

For Europe:
13=0.75mm²/H05VV-F, 23=1.0mm²/H05VV-F

CABLE LENGTH:
For North America: XY=feet, Z=inch
For Europe: X=meter, YZ=cm

Color Options: (Actual color may vary)

 0=Black	 1=Gray	 2=Blue
 3=Purple	 4=Green	 6=Orange
 7=Red	 8=Yellow	 9=White