

FEATURES

- 2nd Generation S-LOCK Securing System
- Unique rotary switch and low profile C13 locking mechanism fits any standard C14 inlet
- Rated up to 15 Amps
- Various colors / length available



TECHNICAL SPECIFICATIONS

| SPECIFICATION | DISCRIPTION |
|-------------------------------|---|
| Standard | IEC 60320 |
| High potential test voltage | 2000VAC (1min 50Hz); 500VDC (1min) |
| Rating | UL/cUL : 10A/13A/15A 250VAC TUV or VDE : 10A 250VAC |
| Operation temperature | -25°C ~ +70°C |
| Flammability corresponding to | Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2 |
| Conductor Size Option | For North America : 18AWG / 16AWG / 14AWG For Europe : 0.75mm ² / 1.0 mm ² |

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



ORDERING INFORMATION

514830 - XX XYZ X

S-Lock Series No.

WIRE TYPE:

For North America:

94=18AWG/SVT, 95=18AWG/SJT
85=16AWG/SJT, 75=14AWG/SJT

For Europe:

13=0.75mm²/H05VV-F, 23=1.0mm²/H05VV-F

CABLE LENGTH:

For North America: XY=feet, Z=inch
For Europe: X=meter, YZ=cm

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White