

**FEATURES**

- 2<sup>nd</sup> Generation S-LOCK Securing System
- Unique rotary switch and low profile C13 locking mechanism fits any standard C14 inlet
- Rated up to 15 Amps
- Various colors / length available



**TECHNICAL SPECIFICATIONS**

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	For North America : 14AWG For Europe : 1.5 mm <sup>2</sup>

**COMMON APPLICATIONS**

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

**APPROVALS**



**ORDERING INFORMATION**

**520830 – XX XYZ X**

**S-Lock Series No.**

---










**WIRE TYPE:**  
For North America:  
75=14AWG/SJT

For Europe:  
33=1.5mm<sup>2</sup>/H05VV-F

---

**CABLE LENGTH:**  
For North America: XY=feet, Z=inch  
For Europe: X=meter, YZ=cm

**Color Options: (Actual color may vary)**

 0=Black	 1=Gray	 2=Blue
 3=Purple	 4=Green	 6=Orange
 7=Red	 8=Yellow	 9=White