

## FEATURES

- 2<sup>nd</sup> Generation S-LOCK Securing System
- Unique rotary switch and low profile C13/C15/C19 locking mechanism fits any standard C14/C16/C20 inlet
- Fully compliance with UL60320
- Hospital Grade NEMA 5-15 plug with green dot for medical devices
- Rated up to 15 Amps
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL817 / UL 60320
High potential test voltage	1250VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 125VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG

## COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

## APPROVALS




## ORDERING INFORMATION

5518XH - XX XYZ X

### S-LOCK TYPE:

3=C13    5=C15    9=C19



### WIRE TYPE:

For North America:

94=18AWG/SVT,    95=18AWG/SJT

85=16AWG/SJT,    75=14AWG/SJT

### CABLE LENGTH:

For North America: XY=feet, Z=inch

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White