

## FEATURES

- Revolutionary positive securing system prevents unintentional power disconnection
- Patented C14 positive mechanism locks with SSEMCO P-Lock outlets and is backward compatible with any standard C13 outlet
- Fit for high density multi-outlets design
- Multi-angle plug option
- Rated up to 15 Amps
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG

### COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

## APPROVALS



## ORDERING INFORMATION

**61415X - XX XYZ X**

**Plug Angle Option**

0=Straight    1=Right    2=Left

3=Up    4=Down

**Color Options: (Actual color may vary)**

0=Black    1=Gray    2=Blue

3=Purple    4=Green    6=Orange

7=Red    8=Yellow    9=White

**WIRE TYPE:**  
For North America:  
94=18AWG/SVT, 95=18AWG/SJT  
85=16AWG/SJT, 75=14AWG/SJT

**CABLE LENGTH:**  
For North America: XY=feet, Z=inch  
For Europe: X=meter, YZ=cm