

## FEATURES

- 2<sup>nd</sup> Generation D-LOCK Securing System
- Unique rotary switch and low profile C13 locking mechanism fits any standard C14 inlet
- Patented C20 positive mechanism locks with SSEMCO P-Lock outlets and is backward compatible with any standard C19 outlet
- Rated up to 15 Amps
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 15A 250VAC TUV or VDE : 10A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1, IEC60332-1. Cat F2
Conductor Size Option	For North America : 14AWG For Europe : 1.5 mm <sup>2</sup>

### COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

## APPROVALS



## ORDERING INFORMATION

**620830 - XX XYZ X**

Dual-Lock Series No.

### WIRE TYPE:

For North America:  
75=14AWG/SJT

### For Europe:

33=1.5mm<sup>2</sup>/H05VV-F

### CABLE LENGTH:

For North America: XY=feet, Z=inch  
For Europe: X=meter, YZ=cm

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White