

FEATURES

- **Patented C14 positive mechanism locks with SSEMCO P-Lock outlets and is backward compatible with any standard C13 outlet**
- **Special single locking clip design for SSEMCO glow and high compact outlet**
- **Rated up to 15 Amps**
- **Various colors / length available**



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



ORDERING INFORMATION










674130 - XX XYZ X

P-Lock Series No.

WIRE TYPE:
For North America:
94=18AWG/SVT, 95=18AWG/SJT
85=16AWG/SJT, 75=14AWG/SJT

CABLE LENGTH:
For North America: XY=feet, Z=inch

Color Options: (Actual color may vary)

 0=Black	 1=Gray	 2=Blue
 3=Purple	 4=Green	 6=Orange
 7=Red	 8=Yellow	 9=White