

## FEATURES

- **Patented C14 positive mechanism locks with SSEMCO P-Lock outlets and is backward compatible with any standard C13 outlet**
- **Special Single Locking Clip Design For SSEMCO glow and high compact outlet**
- **Rated up to 15 Amps**
- **Various colors / length available**



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1
Conductor Size Option	For North America : 14AWG

### COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

## APPROVALS



## ORDERING INFORMATION










**674190 - XX XYZ X**

P-Lock Series No. \_\_\_\_\_

WIRE TYPE:  
For North America:  
75=14AWG/SJT

CABLE LENGTH:  
For North America: XY=feet, Z=inch

Color Options: (Actual color may vary)

		
0=Black	1=Gray	2=Blue
		
3=Purple	4=Green	6=Orange
		
7=Red	8=Yellow	9=White