

FEATURES

- 2nd Generation D-LOCK Securing System
- Unique rotary switch and low profile C15 locking mechanism fits any standard C14&C16 inlet
- Special single locking clip design for SSEMCO glow and high compact outlet
- Rated up to 15 Amps
- Various colors / length available



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	IEC 60320
High potential test voltage	2000VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



ORDERING INFORMATION

674850 - XX XYZ X

Dual-Lock Series No.

WIRE TYPE:

For North America:

94=18AWG/SVT, 95=18AWG/SJT

85=16AWG/SJT, 75=14AWG/SJT

CABLE LENGTH:

For North America: XY=feet, Z=inch

Color Options: (Actual color may vary)



0=Black



1=Gray



2=Blue



3=Purple



4=Green



6=Orange



7=Red



8=Yellow



9=White