

## FEATURES

- 2<sup>nd</sup> Generation S-LOCK Securing System
- Unique rotary switch and low profile C13/C15/C19 locking mechanism fits any standard C14/C16/C20 inlet
- Fully compliance with UL60320
- NEMA L5-15P is commonly used in data centers and different industries for 125V supply.
- Rated up to 15 Amps
- Various colors / length available



## TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL817 / UL 60320
High potential test voltage	1250VAC (1min 50Hz)
Rating	UL/cUL : 10A/13A/15A 125VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1
Conductor Size Option	For North America : 18AWG/16AWG/14AWG

## COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

## APPROVALS



## ORDERING INFORMATION

**7518X0 - XX XYZ X**

**S-LOCK TYPE:**

3=C13    5=C15    9=C19

**WIRE TYPE:**  
For North America:  
94=18AWG/SVT, 95=18AWG/SJT  
85=16AWG/SJT, 75=14AWG/SJT

**CABLE LENGTH:**  
For North America: XY=feet, Z=inch

**Color Options: (Actual color may vary)**

0=Black	1=Gray	2=Blue
3=Purple	4=Green	6=Orange
7=Red	8=Yellow	9=White