

FEATURES

- 2nd Generation S-LOCK Securing System
- Unique rotary switch and low profile C13/C15/C19 locking mechanism fits any standard C14/C16/C20 inlet
- Fully compliance with UL60320
- NEMA L6-15P is commonly used in data centers and different industries for 250V supply.
- Rated up to 15 Amps
- Various colors / length available



TECHNICAL SPECIFICATIONS

SPECIFICATION	DESCRIPTION
Standard	UL817 / UL 60320
High potential test voltage	1250VAC (1min 50Hz)
Rating	UL/cUL : 15A 250VAC
Operation temperature	-20°C ~ +70°C
Flammability corresponding to	Plug/Connector: UL 94V-2 or better Cable: UL VW-1
Conductor Size Option	For North America : 18AWG / 16AWG / 14AWG

COMMON APPLICATIONS

- Data centers
- Medical devices
- Automation Industrial
- Industrial Equipment
- Architectural devices
- Broadcasting stations
- Critical Power Management

APPROVALS



ORDERING INFORMATION

7618X0 - XX XYZ X

S-LOCK TYPE:

3=C13 5=C15 9=C19

WIRE TYPE:
For North America:
94=18AWG/SVT, 95=18AWG/SJT
85=16AWG/SJT, 75=14AWG/SJT

CABLE LENGTH:
For North America: XY=feet, Z=inch

Color Options: (Actual color may vary)

0=Black	1=Gray	2=Blue
3=Purple	4=Green	6=Orange
7=Red	8=Yellow	9=White